

CN 200N SERIES

AUDIO TRANSFORMER ASSEMBLY FOR LF CONDUCTED IMMUNITY TESTING FOR ELECTRICAL VEHICLES



FOR TESTS ACCORDING TO ...

- > ISO 7637-4
- > LV 123
- > VW 80300
- > VW 80303


CN 200N SERIES - SINGLE-BOX TRANSFORMER ASSEMBLY FOR LF CONDUCTED IMMUNITY TESTING

The CN 200N Series is a standalone coupling network unifying up to three audio transformers, each with 100 A capacity, being configurable for various test requirements (e.g. LV 123, ISO/TS 7637-4 draft). The CN 200N Series is used to apply the test signals to the lines under test via an audio transformer to perform ripple voltage tests and continuous or transient conducted immunity tests.

HIGHLIGHTS

- > **Frequency response 10 Hz to 500 kHz**
- > **Secondary saturation up to 300 A (100 A per transformer)**
- > **Audio power up to 3 x 200 W**
- > **Turns ratio 2:1 step down**

APPLICATION AREAS



TECHNICAL DETAILS

MODEL

MODEL OVERVIEW

Audio transformer	
CN 200N100	Secondary Current: 100 A Insulation: 1200 VDC
CN 200N200	Secondary Current: 200 A Insulation: 1200 VDC
CN 200N300	Secondary Current: 300 A Insulation: 1200 VDC

CN 200N100

Secondary current	100 A
Dimension WxDxH	19", 3 HU, 447 mm x 582 mm x 154 mm
Weight	20 kg
Secondary connector	6 mm safety connector, MC 14.0034-21, -22

CN 200N200

Secondary current	200 A
Dimension WxDxH	19", 3 HU, 447 mm x 582 mm x 154 mm
Weight	38 kg
Secondary connector	10 mm safety connector, MC S10 BV-C1

CN 200N300

Secondary current	300 A
Dimension WxDxH	19", 6 HU, 447 mm x 582 mm x 288 mm
Weight	57.4 kg
Secondary connector	16 mm safety connector, MC S16 BV-NS-C1

GENERAL DATA

CHARACTERISTICS AUDIO ISOLATION TRANSFORMERS

Frequency response	10 Hz - 500 kHz
Audio power	200 W per transformer
Turns ratio	2:1 step down


CONNECTORS

Primary connectors	6 mm safety connector, MC 14.0034-21, MC 14.0034-22
--------------------	---

GENERAL DATA

Cooling	passive cooling
Temperature	10°C - 40°C
Rel. humidity	Max. 85%, non-condensing
Atmospheric pressure	86 kPa (860 mbar) to 106 kPa (1,060 mbar)

COMPETENCE WHEREVER YOU ARE



CONTACT EM TEST DIRECTLY

Switzerland

EM TEST (Switzerland) GmbH > Sternenhofstraße 15 > 4153 Reinach > Switzerland
 Phone +41 (0)61/7179191 > Fax +41 (0)61/7179199
 Internet: www.emtest.ch > E-mail: sales.emtest@ametek.com

Germany

AMETEK CTS Germany GmbH > Lünener Straße 211 > 59174 Kamen > Deutschland
 Phone +49 (0)2307/26070-0 > Fax +49 (0)2307/17050
 Internet: www.emtest.com > E-mail: info.cts@ametek.de

France

EM TEST FRANCE > Le Trident - Parc des Collines > Immeuble B1 - Etage 3 > 36, rue Paul Cézanne > 68200 Mulhouse > France
 Phone +33 (0)389 31 23 50 > Fax +33 (0)389 31 23 55
 Internet: www.emtest.fr > E-mail: info@emtest.fr

Poland

EM TEST Polska > ul. Ogrodowa 31/35, 00-893 Warszawa > Polska
 Phone +48 (0)518 64 35 12
 Internet: www.emtest.com/pl > E-mail: infopolska.emtest@ametek.com

USA / Canada

AMETEK Compliance Test Solutions > 52 Mayfield Ave. > Edison > NJ 08837
 Phone +1 (732) 417-0501
 Internet: www.emtest.com > E-mail: sales.emtest@ametek.com

P.R. China

E & S Test Technology Limited > Rm 913, Leftbank > No. 68 Bei Si Huan Xi Lu > Haidian District > Beijing 100080 > P.R. China
 Phone +86 (0)10 82 67 60 27 > Fax +86 (0)10 82 67 62 38
 Internet: www.emtest.com > E-mail: info@emtest.com.cn

Republic of Korea

EM TEST Korea Limited > #405 > WooYeon Plaza > #986-8 > YoungDeok-dong > Giheung-gu > Yongin-si > Gyeonggi-do > Korea
 Phone +82 (31) 216 8616 > Fax +82 (31) 216 8616
 Internet: www.emtest.co.kr > E-mail: sales@emtest.co.kr

Information about scope of delivery, visual design and technical data correspond with the state of development at time of release. Subject to change without further notice.